



PC-667 - Enkeltsidig PE dekket tekstil tape

Description	Enkeltsidig tape bestående av PE dekket Polyester tekstil bærer med kombinert syntetisk / natur gummi lim.
Product properties	Godt feste og heft på de fleste underlag, samt har en vanntett bakside. Er fjernbar etter 2 uker med UV stråling uten limrester. Fleksibel og formbar og lett å rive for hånd. God motstand mot UV stråling.
Applications	Brukes til maskering og beskyttelse av ulike ikke-malte materialer som aluminium, stål, vinyl, gips, stukkatur, betong, keramiske fliser og syntetiske overflater som krever UV beskyttelse.
Storage and ageing	1 år lagringstid dersom lagret i original emballasje og innendørs romtemperetur (+ 20C) samt luftfuktighet 50 %.. Unngå direkte sollys.
Applying tips	Alle overflater skal være rengjort og fri for støv , fett og fukt. For rengjøring anbefales det å bruke Isopropyl - Alkohol oppløsning,og påført med trykk.

TECHNICAL DATA

Carrier	Cloth/PE coated	
Adhesive	Rubber	
Colour	Red	
Liner	None	
UV resistant	Yes	
Thickness Total	0,228 mm	8,98 Mils
Adhesion on stainless steel	13,45 N/25mm	3,07 Lbs/inch
Tensile strength length	94 N/25mm	21,5 Lbs/inch
Elongation length	15 %	
Temperature performance (short time)	93 °C	199 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes Norway A/S
Gamle Drammensvei 120
1363 Høvik
tel +47 - 67 17 79 00
fax +47 - 67 13 84 90
www.stokvistapes.no
info@stokvistapes.no